



US006029461A

# United States Patent [19]

**Zakryk**

[11] **Patent Number:** **6,029,461**  
[45] **Date of Patent:** **Feb. 29, 2000**

[54] **WATER COLLECTION AND DISPENSING MACHINE**

[76] Inventor: **John M. Zakryk**, 5961 SW. 19th St.,  
Plantation, Fla. 33317

[21] Appl. No.: **09/133,694**

[22] Filed: **Dec. 30, 1997**

## Related U.S. Application Data

[63] Continuation of application No. 08/641,186, Apr. 30, 1996,  
Pat. No. 5,701,749.

[51] **Int. Cl.<sup>7</sup>** ..... **F25B 17/06**

[52] **U.S. Cl.** ..... **62/93; 62/150; 62/291**

[58] **Field of Search** ..... 62/92, 93, 271,  
62/78, 150, 285, 288, 291, 264

[56] **References Cited**

## U.S. PATENT DOCUMENTS

3,594,675 7/1971 Willson ..... 337/140  
3,675,442 7/1972 Swanson ..... 62/285  
4,255,937 3/1981 Ehrlich ..... 62/264


5,058,195 10/1991 Knepler ..... 392/442  
5,203,989 4/1993 Reidy ..... 210/137  
5,259,203 11/1993 Engel et al. .... 62/150  
5,669,221 9/1997 LeBleu et al. .... 62/92  
5,701,749 12/1997 Zakryk ..... 62/93

*Primary Examiner*—William Doerrler  
*Attorney, Agent, or Firm*—Malloy & Malloy, P.A.

[57] **ABSTRACT**

A water collection and dispensing machine having a primary housing with an air inlet and an air outlet, an air blower structured to draw air into the primary housing through the air inlet and push air out of said primary housing through the air outlet. The water collection and dispensing machine further includes an evaporator coil structured to cycle a cold refrigerant liquid therethrough, the evaporator coil being disposed in line with the air inlet so that the air drawn into the primary housing through the air inlet passes there over and moisture therefrom condenses on an exterior surface of the evaporator coil so that it may be collected in the form of water droplets, filtered to eliminate contaminants, and dispensed for convenient consumption by a user.

**20 Claims, 3 Drawing Sheets**






FIG. 1





FIG. 2



## WATER COLLECTION AND DISPENSING MACHINE

The present application is a continuation-in-part application of previously filed, now allowed patent application having Ser. No. 08/641,186 filed on Apr. 30, 1996 and due to issue as U.S. Pat. No. 5,701,749 on Dec. 30, 1997.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to a water collection and dispensing machine which is capable of effectively and efficiently collecting drinkable water from the atmosphere in an assembly that is substantially compact and quiet, yet capable of producing sufficiently large quantities of water to satisfy normal consumption requirements, and in an assembly that is substantially durable and free from malfunction, such as those related to excess moisture and icing.

#### 2. Description of the Related Art

The availability of fresh, purified drinking water is highly desirable in virtually every environment and circumstance. For example, individuals in homes and offices often install complex and expensive filtration systems, or buy small individual bottles of spring water for personal consumption purposes. One of the most common manners in which purified drinking water is made available, however, involves the utilization of large 5-gallon water bottles in conjunction with a cooler assembly.

While the use of the larger bottles with a cooler is generally more convenient to implement than other methods of providing purified water, anyone who has been charged with the task of replacing an empty water bottle is very aware of the difficulties and inconveniences associated with the use of conventional bottled water cooler systems. First of all, the large bottles of water are generally heavy, and as such, quite difficult for any person to lift and position atop of the cooler. Moreover, the bottle must not merely be lifted onto a top of the cooler, but rather, it must be turned upside-down, with the spout open, so as to permit for the availability of the water contained therein. Inevitably, individuals changing the water bottle spill quantities of water, which may be hazardous and make for a slippery environment, or end up getting hurt while changing the bottle due to the heavy weight that must be manipulated.

In addition to the substantial difficulties associated with reloading conventional water coolers, the cost associated with the frequent purchase of the large bottles can add up and become quite expensive, especially when aggregated with the electrical cost associated with operating the cooler. Further, if limited space is available, the large inverted water bottle, which has a generally unattractive appearance, takes up a lot of excess space and will generally not permit the use of the space over the water cooler for alternative purposes.

As such, it would be highly beneficial to provide a water cooler type assembly which is capable of providing sufficient quantities of purified, drinkable water, without requiring that a large water bottle be implemented to supply the water. Such a device would preferably take up less space, would be more cost effective, would not require water bottle replacement, and would not require frequent water deliveries to ensure that water is always available for drinking purposes. Indeed, such a device would be highly beneficial in environments when drinking water is scarce or otherwise not available.

In the past, others have attempted to provide various complex and elaborate mechanisms for producing potable

water from the atmospheric air. Generally, such devices are designed for use at locations where the water supply is limited and individuals need drinking water to survive. As a result, cost, size, noise, and other ergonomic features which would make the devices convenient for use on an everyday basis are not primary considerations in their design. Accordingly, such devices could not be effectively utilized in a home or office setting in order to practically and effectively replace the use of conventional bottled water coolers.

In addition to those larger, highly complex devices, other devices for the extraction of potable water from the atmosphere such as that disclosed in the patent to Engel et al. (U.S. Pat. No. 5,259,203) have attempted to provide a more readily useable device. Such devices, however, still do not achieve maximum efficiency and effectiveness for use and are not as suited for use in an office or home environment. For example, such devices generally rely on a gravity feed, and as a result must be mounted in a generally elevated orientation to permit effective access to a spigot thereof. Moreover, fluid which is ready to be dispensed may remain within dispensing tubing or a reservoir for extended periods of time and as a result, may become stagnate or otherwise contaminated. Additionally, such devices often have limited capacity and are quite noisy which tends to diminish their desirability of use within an office or home environment.

A further drawback associated with existing devices is their susceptibility to malfunction, such as from corrosion or internal icing. For example, the nature of these types of devices provides that large quantities of moisture are formed and collect internally, especially if cooling is involved. Unfortunately, all of the moisture does not form in the desired collection areas and as a result internal electrical components and other components are susceptible to corrosion, water damage and or contamination from stagnant moisture build ups. Moreover, if the temperature within these devices is not regulated effectively and accurately, internal icing can result when attempting to maintain the water at a desired, cool drinking temperature.

There therefore still a substantial need in the art for an effective and efficient water cooling type system which has a sufficient water capacity for effective use, maintains water fresh and readily available at all times without contamination and at a desirable cooled temperature, is substantially inexpensive to operate, and is conveniently useable in a home or office environment as a result of its compact nature, relatively quiet operation, and convenient dispensing. Moreover, such a device should be relatively free from corrosion or internal icing and should be configured so as to facilitate the maintenance of maximum purification conditions at all times.

### SUMMARY OF THE INVENTION

The present invention is directed towards a water collection and dispensing machine structured to provide a quantity of purified, drinkable water, for convenient consumption. The water collection dispensing machine includes a primary housing, which is preferably somewhat compact and has an air inlet and an air outlet. Specifically, the air outlet is preferably disposed at generally a bottom of the housing to provide for convenient, out of the way release of air there-through. Further, the water collection and dispensing machine includes an air blower. The air blower is structured to draw air into the primary housing through the air inlet, and thereby create a positive pressure condition within the primary housing. That positive pressure that is created

within the primary housing in turn pushes air through the primary housing and down and out of it through the air outlet in a relatively quiet fashion.

Additionally, the water collection and dispensing machine includes a dehumidifier refrigerant assembly. Specifically, the dehumidifier refrigerant assembly is structured and disposed to convert a refrigerant gas into a cold refrigerant liquid. That cold refrigerant liquid is then to be cycled through an evaporator coil disposed within the primary housing. The evaporator coil is specifically structured so that the air that is drawn into the primary housing through the air inlet will pass there over as it flows through the primary housing to the air outlet. As a result, moisture from the air passing over the evaporator coil condenses on an exterior of the coil where it can be collected, in the form of water droplets, by a fluid collection assembly. Preferably, the fluid collection assembly includes a fluid reservoir wherein a substantial amount of water is contained for dispensing.

Furthermore, the water collection and dispensing machine may include a cooling assembly. Specifically, the cooling assembly is structured to cool the water contained in the fluid reservoir to a predetermined cooled temperature. Moreover, so as to identify a temperature of that water, a temperature detection assembly is provided and functions to direct a cooling operation of the cooling assembly. The temperature detection assembly itself includes a detection head that is structured to be immersed within the water contained in the fluid reservoir, thereby providing a substantially accurate temperature identification. Moreover, the temperature detection assembly includes a shielding assembly which communicably shields the detection head from contact with the water, and thereby protects the detection head from rusting or deteriorating into the water, while still permitting a temperature of the water to be identified.

Preferably, the water collection and dispensing machine also includes a filtration assembly. Specifically, the filtration assembly is structured to filter the collected water prior to dispensing. Moreover, the filtration assembly of the present invention includes a pump structured to draw water from the fluid reservoir, a water filter structured to receive the water therethrough for filtration, and an insulation assembly. The insulation assembly is structured to enclose and insulate the pump and water filter from condensation and moisture, thereby preventing rusting and deterioration thereof.

It is an object of the present invention to provide a water collection and dispensing machine which accurately and efficiently maintains drinking water at a predetermined cooled temperature, with minimal risk of internal icing or water contamination due to corrosion and the like.

An added object of the present invention to provide a water collection and dispensing machine which isolates excess moisture and condensation from internal components which are susceptible to corrosion and deterioration as a result of the moisture.

Also an object of the present invention is to provide a water collection and dispensing machine which provides for facilitated repair and replacement of filtration components, thereby minimizing a risk of long term malfunction and maximizing the purity of the dispensed water by facilitating the maintenance of fresh filtration cartridges.

Another object of the present invention to provide a water collection and dispensing machine which has increased fluid retention capacity and is convenient to utilize in a work or home environment.

A further object of the present invention is to provide a water collection and dispensing machine which is substantially compact and quiet during operation.

Still another object of the present invention is to provide a water collection and dispensing machine that does not require the use of large water bottles while still providing sufficient quantities of fluid for normal consumption.

Yet another object of the present invention is to provide a water collection and dispensing machine which maintains water to be dispensed cool without requiring a second refrigerant system.

A further object of the present invention is to provide a water collection and dispensing machine which effectively circulates water therethrough to ensure that water to be dispensed is not stale and has not remained stagnant for extended periods of time.

Also an object of the present invention is to provide a water collection and dispensing machine which dispenses substantially clean, purified water without requiring connection with a conventional water source such as a tap or water bottle in order to provide quantities of purified water.

## BRIEF DESCRIPTION OF THE DRAWINGS

For a fuller understanding of the nature of the present invention, reference should be had to the following detailed description taken in connection with the accompanying drawings in which:

FIG. 1 is a front cross-sectional view of the water collection and dispensing machine of the present invention;

FIG. 2 is a side cross-section view of the water collection and dispensing machine of the present invention; and

FIG. 3 is a front cross-sectional view of a preferred embodiment of the water collection and dispensing machine of the present invention.

Like reference numerals refer to like parts throughout the several views of the drawings.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention is directed towards a water collection and dispensing machine, generally indicated as **10**. In particular, the water collection and dispensing machine **10** is structured to draw in atmospheric air, and convert the humidity contained therein into purified, drinkable water. As such, included as part of the water collection and dispensing machine **10** is a primary housing **20**. This primary housing **20**, which may be formed of aluminum, plastic or any other suitable, rigid or semi-rigid material is preferably somewhat compact and contains the remaining components of the water collection and dispensing machine **10** conveniently therein. Accordingly, the primary housing **20** provides the attractive exterior appearance for the water collection and dispensing machine **10** and its finished and compact nature facilitates the positioning of the water collection and dispensing machine **10** in a convenient, out of the way, space maximizing location.

The primary housing **20**, which preferably includes a rectangular type configuration, includes generally an open interior area **22**, an air inlet **24**, and an air outlet **26**. In use, air is structured to flow into the primary housing **20** through the air inlet **24**, pass through the interior area **22** and exit through the air outlet **26**. Further, in the preferred embodiment, the air inlet is disposed generally at an upper, rear portion of the primary housing **20**, such as at a side of the primary housing **20** facing a wall against which the primary housing **20** is disposed. Accordingly, air can effectively be drawn into the primary housing **20** through the rear thereof, while still achieving generally quiet introduction of

the air into the primary housing **20** as the noise at the air inlet is directed towards a wall and is thereby somewhat muffled.

Furthermore, in the preferred embodiment, the air outlet **26** is disposed at a base or bottom portion of the primary housing **20**. As such, the air drawn in through the air inlet **24** flows completely through the primary housing **20** and can be efficiently utilized for a variety of functions without requiring significant redirection of its flow, and the air exiting the primary housing **20**, which is generally somewhat warm, is more readily dissipated beneath the primary housing **20**. Further, much like results with the positioning of the air inlet **24** towards a wall surface, the positioning of the air outlet **26** generally against the floor on which the primary housing **20** is disposed functions to somewhat muffle noises within the primary housing **20** and helps to contribute to the overall quite operation of the water collection and dispensing machine **10**.

Disposed within the primary housing **20** and structured to draw air from the atmosphere into the primary housing **20** is an air blower **30**. The air blower **30** may be any conventional type of extractor type blower which draws the air into the primary housing **20** through the air inlet **24**, and in turn creates a positive pressure condition within the interior **22** of the primary housing **20**. It is that positive pressure that pushes the air back out through the air outlet **26** against the floor, and further facilitates the exceptionally quiet operation of the water collection and dispensing machine **10**.

Further contained within the primary housing **20** is a dehumidifier refrigerant assembly. The dehumidifier refrigerant assembly is specifically structured and disposed to convert a refrigerant gas into a cold refrigerant liquid. As such, in the preferred embodiment the dehumidifier refrigerant assembly includes a compressor **35**. The compressor **35** is structured to compress a refrigerant gas contained therein and thereby form a very hot gas. This very hot gas is then transferred into a condenser coil **36**. The condenser coil **36** receives the hot gas from the compressor **35** and is disposed directly in-line with the air outlet **26** so that cooled air which exits the primary housing **20** through the air outlet **26** necessarily passes over the condenser coil **36**. As a result, a substantial quantity of heat is drawn off of the condenser coil **36** by the cool air flow, resulting in the cooling of the very hot gas into a cool liquid. Further connected with the condenser coil **36** as part of the dehumidifier refrigerant assembly is a cap tube **38**, or optional TXV. The cap tube **38** is connected in fluid flow communication with the condenser coil **36** and permits the cooled liquid to further expand as it flows therethrough and accordingly create a cold liquid. The cold liquid then flows from the cap tube **38** into an evaporator coil **40**.

Looking specifically to the evaporator coil **40**, it is preferably a fin and tube evaporator coil connected in fluid flow communication with the cap tube **38** and structured to cycle the cold liquid therethrough. As a result of this specific structure of the fin and tube evaporator coil **40**, the cold refrigerant liquid is maintained therein for a substantial period of time and the overall exterior surface area of the evaporator coil **40** is maximized. Preferably, the fin and tube evaporator coil **40** is formed of a metallic material, such as copper so that the cold liquid flowing therethrough makes the surface of the evaporator coil **40** substantially cold as well. Moreover, the evaporator coil **40** is preferably disposed in line with the air inlet **24** in the primary housing **20**. As such, upon air being drawn into the primary housing **20** by the air blower **30** it passes over the evaporator coil **40**. Due to the cold temperature of the evaporator coil **40**, as the air flow comes into contact with the exterior surface thereof,

moisture contained within the air condenses on the evaporator coil **40** in the form of water droplets.

Disposed beneath the evaporator coil **40**, and preferably included as part of the fluid collection assembly of the present invention, is a drip tray **42**. The drip tray **42** is disposed beneath an entire surface of the evaporator coil **40** such that as the moisture, which was collected from the air on the exterior surface of the evaporator coil **40** drips down from the evaporator coil in the form of the water droplets, those water droplets are collected by the drip tray **42**. The drip tray **42** is in turn connected by an elongate fluid conduit **43** with a generally large fluid reservoir **45**. The fluid reservoir **45** preferably has a somewhat large capacity to ensure that sufficient quantities of water are available for dispensing purposes. Also, the fluid reservoir **45** can be disposed in line with the air flow passing through the primary housing **20** such that the air, which has been cooled as it passed over the evaporator coil **40**, can function to cool the water within the fluid reservoir **45**.

In order to provide purified, drinkable water for consumption by individuals, the water collection and dispensing machine **10** further includes filtration assembly. The filtration assembly is structured to ensure that all of the water collected is free from contaminants, which may be present in the air as it enters the primary housing **20**. In this regard, and as an initial means of filtration, an air intake filter **47** is disposed generally over the air inlet **24**. Accordingly, utilizing the air inlet filter **47** a substantial amount of particulates are removed from the air, thereby minimizing the contaminants which will be present in the water droplets which are drawn from the air. Still, however, as the water is collected in the drip tray **42** and passed into the fluid reservoir **45**, some contaminants may still be present within the water. As a result, the filtration assembly of the present invention further includes a water filter **50** contained within the primary housing **20**. The water filter **50** is structured to receive water therethrough as a result of a pump **52** also contained within the primary housing **20**. In particular, the pump **52** through an elongate conduit **53** draws water from the fluid reservoir **45** and pumps it into the water filter **50**. The water filter **50** itself may include any kind of conventional water filtration and purification means, and furthermore, in the preferred embodiment will also include UV light to provide further purification. Specifically, and turning to FIG. **3**, the preferred embodiment of the filtration assembly includes both a first water filter **50'**, such as a carbon filter tube, and a second water filter **50''**, such as a UV light filter. Moreover, it is preferred that the pump **52** and one or more water filters **50'** and **50''** be disposed in generally closely spaced relation with one another within an insulation assembly **51**. The insulation assembly **51** is preferably a foam lined container which completely encloses and contains the pump **52** and water filters **50'** and **50''**, thereby insulating them from moisture and condensation which can build up during the water formation. Indeed, it is noted that with the excess moisture that is naturally present within the machine **10** of the present invention, various components, and especially the electrical pump, can be susceptible to corrosion and deterioration. As such, the insulation assembly **51** keeps out moisture, dirt and condensation, providing only for the fluid flow conduits to pass into and out of the enclosed insulation assembly **51**. As a further convenience, in the preferred embodiment, the insulation assembly **51**, and therefore the pump **52** and any water filters contained therein, is removably coupled to the primary housing **20** in a manner which facilitates removal, repair and/or replacement of the various components. In particular, it is noted that

the pump may require routine maintenance procedures and the water filters must be cleaned and or replaced on a regular basis. As such, a service technician can arrive at a machine **10** with a replacement insulation assembly **51**, can uncouple the water flow conduits and other minor connections to release the insulation assembly and replace it with a fresh one. Of course, if desired, the water filters may be independently removable from the insulation assembly **51** if more frequent replacement is necessary, and/or the water filters may be disposed within their own insulation assembly so as to provide for independent removal.

Extending from the water filter **50** is a further conduit **54** which permits the water to be pumped from the water filter **50** into a delivery coil **55**. Moreover, the delivery coil **55** is structured to contain a quantity of filtered water in a ready to dispense orientation such that a user need not wait for completion of the filtration process. Indeed, some form of level indication may be provided such that when water is depleted from the delivery coil **55**, the pump **52** draws more water from the fluid reservoir for filtration.

As it is preferred that the water dispensed from the water collection and dispensing machine **10** of the present invention be cool, further included within the primary housing **20** is a cooling assembly structured to maintain the water at a predetermined cooled temperature. Although a second refrigeration system may also be incorporated within the primary housing **20**, in the preferred embodiment the fluid reservoir **45** is lined with a plurality of thermal electric cold plates **57**. These thermal electric cold plates **57** function to maintain the water in the fluid reservoir **45** substantially cool without requiring the added noise, cost and energy of a separate refrigeration system solely for water cooling purposes. Additionally, so as to maximize the cooling effects of the cold plates **57**, the delivery coil **55** is preferably structured to be maintained submerged beneath the water level within the fluid reservoir **45**. Moreover, the delivery coil **55** will preferably be constructed of a temperature conductive material, such as copper so that the purified water maintained therein is maintained cool as a result of its presence in the cool environment of the fluid reservoir **45**.

With either cooling assembly, it is preferred that constant cooling not be permitted so as to prevent icing or freezing within the machine **10**. As such, a cooling operation of the cooling assembly is regulated by a temperature detection assembly. The temperature detection assembly is structured to detect a temperature of the water within the fluid reservoir **45**. In the preferred embodiment, the temperature detection assembly includes a detection head **80**. Preferably the detection head **80** is in the form of a thermistor, and although it may be placed outside the walls of the fluid reservoir **45** or merely in proximity to the water, it is preferred that the detection head be immersed within the water contained in the fluid reservoir. Specifically, it is noted that unless direct and accurate temperature detection is achieved, excessive or insufficient cooling can result, especially since the walls of the fluid reservoir **45** and the ambient air around the water will generally be at very different temperatures from the water. Because, however, the detection head **80** will generally be metallic, and accordingly will be susceptible to rusting or corrosion after extended periods of time submerged in water, the temperature detection assembly of the present invention further includes a shielding assembly **82**. The shielding assembly **82** is structured to communicably shield the detection head **80** from the water so as to prevent rusting and deterioration thereof, while also permitting the temperature of the water to be accurately and readily detected by the detection head **80**. in the preferred

embodiment, the shielding assembly **82** includes an elongate tubular shaft, such as formed from plastic or another material which will not substantially hamper temperature detection, disposed in the fluid reservoir **45**. Moreover, a distal end **83** of the shaft **82**, wherein the detection head **80** is preferably disposed, is positioned at generally a lower region of the fluid reservoir so as to ensure that it will almost always be submerged in the water. Conversely, the proximal end **84** of the shaft **82** will be positioned generally above a fluid level within the fluid reservoir **45**, and is preferably mounted to an upper surface of the fluid reservoir **45** so as to maintain a constant position of the shaft **82**. Furthermore, the proximal end **84** of the shaft **82** preferably includes an opening wherethrough an elongate conductive element **85**, such as a wire, which is connected with the detection head **80**, may pass. For example, the detection head **80** is preferably communicably connected by the elongate conductive element **85** to a control assembly **86** of the temperature detection assembly so as to give the necessary temperature readings for subsequent direction of the cooling of the cooling assembly by the control assembly **86**.

Looking further to the delivery coil **55**, it is preferably a substantially elongate coiled tube so that a substantial quantity of the purified water may be maintained therein in a ready to dispense orientation. Further, the outlet of the delivery coil **55** preferably includes a Y connection **60**. The Y connector **60** is structured to permit water flow either to a dispensing spigot **65** or a return tube **68**. Looking first to the dispensing spigot **65**, it is connected to the delivery coil **55** by an elongate conduit **62**. As a result of the pump **52** which pumps the water through the water filter **50** and into the delivery coil **55**, the purified ready to dispense water is pumped up the conduit **62** to the dispensing spigot **65** and is ready to be dispensed when needed. Much like conventional water dispensing devices, the dispensing spigot **65** is preferably a conventional on/off type tap wherein a lever **64** is actuated so as to open up a valve within the dispensing spigot **65** and permit water to flow therefrom for effective dispensing. It should be understood, however, that any alternative means of dispensing could equivalently be employed. Extending from a second outlet of the Y connector **60** is a secondary conduit **63**. This second conduit **63** is connected in fluid flow communication with the return tube **68** through valve assembly **70**. The valve assembly **70** is specifically structured and disposed to open on a predetermined, regulated basis in order to permit selective cycling of the quantity of filtered water contained within the delivery coil **55** into the return tube **68**. In particular, the return tube **68** is connected in fluid flow communication back to the fluid reservoir **45**. As such, if after a predetermined period of time or after a predetermined number of uses, some purified water has remained within the delivery coil **55** for an extended period, that water is cycled back into the fluid reservoir **45**. Such cycling ensures that the quantity of water that is ready to be dispensed within the delivery coil **55** is always freshly filtered and has not been allowed to be maintained within the delivery coil **55** for an extended period of time whereafter it may become stagnant or otherwise less desirable to drink. In the preferred embodiment the valve assembly **70** includes a timed solenoid valve structured to open based upon a predetermined timed cycle. For example, the solenoid valve **70** may be structured to either open every few minutes and direct the fluid back into the fluid reservoir **45**, or to open if fluid has not been dispensed after a predetermined number of minutes through the dispensing spigot **65**. Accordingly, water can be maintained constantly filtered.

As a further feature of the present invention, also included within the fluid reservoir **45** is preferably a fluid level detection assembly **49**. Specifically, the fluid level detection assembly **49** is structured and disposed to detect whether a level of water within the fluid reservoir **45** is too high or too low and correspondingly regulate operation of the machine. For example, if the water level drops too low it may serve as an indication for the shutdown of the thermal cold plates **57**, such that energy is not wasted, and can initiate an extended water producing cycle to refill the fluid reservoir **45** back to an acceptable level. More commonly, however, the fluid level detection assembly will preferably function to detect when a fluid level is reaching the maximum capacity of the fluid reservoir **45**. As a result, when that water level is detected as being too high, the air blower **30** and dehumidifier refrigerant assembly will not need to operate to produce further water. Such a configuration saves electricity and ensures that operation does not result in an overflow of the fluid reservoir **45**. Furthermore, so as to maintain maximum efficiency of the dehumidifier refrigerant assembly, it also includes a recycling assembly. Specifically, the recycling assembly is structured to recycle the cold liquid from the evaporator coil **40** and direct it back to the compressor **35** in the form of refrigerant gas once again. As such, the recycling assembly includes a return conduit **72** which directs the cold liquid **40** from the evaporator coil into the compressor **35**, permitting the cold liquid to return to its normal refrigerant gas state whereafter the cycle may repeat itself beginning at the compressor **35**. Additionally, if necessary, the back surface of the primary housing **20** may include a refrigerant system static condenser **75**. This static condenser **75** may be used either as a condenser coil for a secondary refrigeration cycle used to cool the water within the fluid reservoir **45**, or to provide for the return of the cold liquid from the evaporator coil **40** to the condenser **35** therethrough so as to further facilitate its return to its conventional refrigerant gas state.

It is therefore seen that given the specific structure of the water collection and dispensing machine **10** of the present invention, the production of water is substantially facilitated, without requiring large water bottles be implemented, in a substantially quite and efficient manner.

Since many modifications, variations and changes in detail can be made to the described preferred embodiment of the invention, it is intended that all matters in the foregoing description and shown in the accompanying drawings be interpreted as illustrative and not in a limiting sense. Thus, the scope of the invention should be determined by the appended claims and their legal equivalents.

Now that the invention has been described,

What is claimed is:

1. A water collection and dispensing machine comprising:
  - a primary housing, said primary housing including an air inlet and an air outlet,
  - an air blower structured to draw air into said primary housing through said air inlet,
  - a dehumidifier refrigerant assembly structured and disposed to convert a refrigerant gas into a cold refrigerant liquid,
  - an evaporator coil structured to cycle said cold refrigerant liquid therethrough, said evaporator coil being disposed such that the air drawn into said primary housing through said air inlet passes over said evaporator coil and moisture therefrom condenses on an exterior of said evaporator coil,
  - a fluid collection assembly structured to collect said moisture, in the form of water droplets, from said evaporator coil,

said fluid collection assembly including a fluid reservoir structured and disposed to contain said water for dispensing,

a filtration assembly structured and disposed to filter said water collected by said fluid collection assembly prior to dispensing, and

said filtration assembly comprising:

- a pump structured to draw said water from said fluid reservoir,

- a water filter structured to receive said water drawn by said pump therethrough for filtration thereof, and
- an insulation assembly structured to enclose and insulate said pump and said water filter from condensation and moisture so as to substantially prevent rusting and deterioration thereof.

2. A water collection and dispensing machine as recited in claim **1** wherein said insulation assembly, and accordingly said pump and said water filter contained therein, are structured to be removably coupled to said primary housing so as to facilitate repair and replacement thereof.

3. A water collection and dispensing machine as recited in claim **2** wherein said water filter of said filtration assembly further includes a UV light filter contained by said insulation assembly and structured to further purify water flowing through said water filter.

4. A water collection and dispensing machine as recited in claim **2** wherein said water filter includes a carbon filter.

5. A water collection and dispensing machine as recited in claim **4** wherein said carbon filter is removably coupled within said insulation assembly.

6. A water collection and dispensing machine as recited in claim **2** wherein said insulation assembly includes an enclosed, substantially foam lined container.

7. A water collection and dispensing machine as recited in claim **1** wherein said filtration assembly including a delivery coil structured to contain a quantity of filtered water in a ready to dispense orientation.

8. A water collection and dispensing machine as recited in claim **7** further including a dispensing spigot connected with said delivery coil and structured to selectively dispense the quantity of water from said delivery coil,

- a return tube, said delivery coil being connected in fluid flow communication with said dispensing spigot and said return tube, and

- said return tube being connected in fluid flow communication with said fluid reservoir and including a valve assembly structured and disposed to open on a predetermined, regulated basis in order to selectively cycle said quantity of filtered water back into said fluid reservoir and thereby ensure that water in said delivery coil is fresh.

9. A water collection and dispensing machine as recited in claim **7** wherein said delivery coil is disposed in said fluid reservoir such that the quantity of water contained therein is maintained cold.

10. A water collection and dispensing machine as recited in claim **1** wherein said evaporator coil includes a fin and tube evaporator coil.

11. A water collection and dispensing machine as recited in claim **1** wherein said air inlet is disposed at generally an upper, rear portion of said housing.

12. A water collection and dispensing machine as recited in claim **1**, further comprising a cooling assembly structured and disposed to cool said water disposed in said fluid reservoir to a predetermined cooled temperature.

13. A water collection and dispensing machine as recited in claim **12**, further comprising a temperature detection

## 11

assembly structured and disposed to identify a temperature of said water in said fluid reservoir and direct a cooling operation of said cooling assembly so as to achieve said predetermined cooled temperature.

**14.** A water collection and dispensing machine as recited in claim **13** wherein said temperature detection assembly includes a detection head structured to be emersed in said water contained in said fluid reservoir.

**15.** A water collection and dispensing machine as recited in claim **14** further comprising a shielding assembly structured to communicably shield said detection head from said water so as to prevent rusting and deterioration thereof, while also permitting the temperature of said water to be readily detected by said detection head so as to correspondingly direct said cooling operation of said cooling assembly.

**16.** A water collection and dispensing machine as recited in claim **12** wherein said cooling assembly includes a plurality of thermal electric cold plates lining said fluid reservoir and structured and disposed to maintain said water within said fluid reservoir cold.

## 12

**17.** A water collection and dispensing machine as recited in claim **14** wherein said detection head includes a thermistor coupled by at least one elongate conductive element to said temperature detection assembly.

**18.** A water collection and dispensing machine as recited in claim **15** wherein said shielding assembly includes an elongate, generally tubular shaft structured to receive said detection head therein.

**19.** A water collection and dispensing machine as recited in claim **18** wherein said shaft is disposed in said fluid reservoir with a distal end thereof disposed at generally a lower region of said fluid reservoir and a proximal end thereof disposed above a level of said water contained in said fluid reservoir.

**20.** A water collection and dispensing machine as recited in claim **19** wherein said detection head is disposed at generally said distal end of said shaft, and said conductive element extends from said shaft at generally said proximal end thereof.

\* \* \* \* \*